

EUROPEAN SAFETY DATA SHEET

SAFETY DATA SHEET

Page 1 of 4

HumiSeal 1A33

Revision 6
Revision date 26-Jul-2006

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name HumiSeal 1A33

Company HumiSeal Europe
Alasan House
Albany Park
Frimley Road
Camberley
Surrey
GU16 7PH
United Kingdom

Telephone +44 (0)127 6691100

Fax +44 (0)127 6691227

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Toluene	1-10%	108-88-3	203-625-9	F; R11 Repr Cat 3; R63 Xn; R48/20-65 Xi; R38 R67
Butanone (Butan-2-one (methyl ethyl ketone))	1-10%	78-93-3	201-159-0	F; R11 Xi; R36 R66 R67
Ethylbenzene	1-10%	100-41-4	202-849-4	F; R11 Xn; R20
Xylene (Xylene, o-,m-,p-or mixed isomers)	30-40%	1330-20-7	215-535-7	R10 Xn; R20/21 Xi; R38

3. HAZARDS IDENTIFICATION

Main hazards Highly flammable. Harmful by inhalation and in contact with skin. Irritating to skin.

4. FIRST AID MEASURES

Skin contact Wash off immediately with plenty of soap and water.

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.

Inhalation Move the exposed person to fresh air.

Ingestion DO NOT INDUCE VOMITING. Seek medical attention.

General information Immediate medical attention is required.

Manufactured by: Humiseal Europe,
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
Phone: 44-127-669-1100 Fax: 44-127-669-1227

Print date 26-Jul-2006

HumiSeal 1A33

Revision 6
Revision date 26-Jul-2006

5. FIRE FIGHTING MEASURES

Extinguishing media Use as appropriate: carbon dioxide (CO₂), dry chemical, foam.

Protective equipment Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure adequate ventilation of the working area.

Environmental precautions Do not allow product to enter drains.

Clean up methods Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

7. HANDLING AND STORAGE

Handling Ensure adequate ventilation of the working area.

Storage Store in original container. Store at temperatures between 5 °C and 25 °C. Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Toluene	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 150	WEL 8-hr limit mg/m ³ : 191 WEL 15 min limit mg/m ³ : 574
Butanone (Butan-2-one (methyl ethyl ketone))	WEL 8-hr limit ppm: 200 WEL 15 min limit ppm: 300	WEL 8-hr limit mg/m ³ : 600 WEL 15 min limit mg/m ³ : 899
Ethylbenzene	WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 125	WEL 8-hr limit mg/m ³ : 441 WEL 15 min limit mg/m ³ : 552
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m ³ : 220 WEL 15 min limit mg/m ³ : 441

Respiratory protection Wear suitable respiratory equipment when necessary. Wear: Suitable respiratory equipment.

Hand protection Chemical resistant gloves (PVC)

Eye protection Avoid contact with eyes. In case of splashing, wear: Safety glasses.

Protective equipment Avoid contact with eyes and skin.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description Liquid.

Colour Amber.

Odour Aromatic.

Flash point 3°C

10. STABILITY AND REACTIVITY

Stability Stable.

Materials to avoid Strong oxidising agents.

Hazardous decomposition products Carbon oxides.

Manufactured by: Humiseal Europe,
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
Phone: 44-127-669-1100 Fax: 44-127-669-1227

Print date 26-Jul-2006

HumiSeal 1A33

Revision 6
Revision date 26-Jul-2006

11. TOXICOLOGICAL INFORMATION

Corrosivity Irritating to eyes, respiratory system and skin.

Repeated or prolonged exposure Repeated or prolonged exposure may cause dermatitis.

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

General information Dispose of as special waste in compliance with local and national regulations.

14. TRANSPORT INFORMATION

ADR/RID

Proper Shipping Name PAINT **UN** 1263

Packing group II **Class** 3

Hazard ID 33

IMDG

UN 1263 **Packing group** II

Class 3 **Marine pollutant** .

EmS Code F-E S-E

IATA

UN 1263 **Packing group** II

Class 3 **Subsidiary risk** -

Packing Instruction 307 **Maximum quantity** 60 L
(Cargo)

Packing Instruction 305 **Maximum quantity** 5 L
(Passenger)

15. REGULATORY INFORMATION

Symbols F - Highly flammable; Xn - Harmful



Risk phrases R11 - Highly flammable.
R20/21 - Harmful by inhalation and in contact with skin.
R38 - Irritating to skin.

Safety phrases S16 - Keep away from sources of ignition - No smoking.
S36/37 - Wear suitable protective clothing and gloves.

Manufactured by: Humiseal Europe,
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
Phone: 44-127-669-1100 Fax: 44-127-669-1227

Print date 26-Jul-2006

HumiSeal 1A33

Revision 6
Revision date 26-Jul-2006

16. OTHER INFORMATION

Text of risk phrases in Section 2	R10 - Flammable. R11 - Highly flammable. R20 - Harmful by inhalation. R20/21 - Harmful by inhalation and in contact with skin. R36 - Irritating to eyes. R38 - Irritating to skin. R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation. R63 - Possible risk of harm to the unborn child. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.
Further information	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. The information provided relates only to the product or material specified and does not apply if used in combination with other materials. Handle and store under inert gas. This product is not properly labelled for sale or use outside the EU.
Revision	This document differs from the previous version in the following areas: 9 - flash point.

**Manufactured by: Humiseal Europe,
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
Phone: 44-127-669-1100 Fax: 44-127-669-1227**

Print date 26-Jul-2006