

## EUROPEAN SAFETY DATA SHEET

### SAFETY DATA SHEET

Page 1 of 3

### HuiSeal 1R32A-2

Revision 2  
Revision date 4-Aug-2006

#### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

**Product name** HuiSeal 1R32A-2

**Company** HumiSeal Europe  
Alasan House  
Albany Park  
Frimley Road  
Camberley  
Surrey  
GU16 7PH  
United Kingdom

**Telephone** +44 (0)127 6691100

**Fax** +44 (0)127 6691227

#### 2. COMPOSITION / INFORMATION ON INGREDIENTS

##### Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Butanone (Butan-2-one (methyl ethyl ketone))	10 - 20%	78-93-3	201-159-0	F; R11 Xi; R36 R66 R67
n-Butyl acetate (Butyl acetate)	40 - 50%	123-86-4	204-658-1	R10 R66 R67

#### 3. HAZARDS IDENTIFICATION

**Main hazards** Highly flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

#### 4. FIRST AID MEASURES

**Skin contact** Wash off immediately with plenty of soap and water.

**Eye contact** Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.

**Inhalation** Move the exposed person to fresh air.

**Ingestion** DO NOT INDUCE VOMITING. Seek medical attention.

**General information** Immediate medical attention is required.

#### 5. FIRE FIGHTING MEASURES

**Extinguishing media** Use as appropriate: carbon dioxide (CO<sub>2</sub>), dry chemical, foam.

**Protective equipment** Wear suitable respiratory equipment when necessary.

**Manufactured by: Humiseal Europe,  
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England  
Phone: 44-127-669-1100 Fax: 44-127-669-1227**

Print date 4-Aug-2006

# HuiSeal 1R32A-2

Revision 2  
Revision date 4-Aug-2006

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Ensure adequate ventilation of the working area.
<b>Environmental precautions</b>	Do not allow product to enter drains.
<b>Clean up methods</b>	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Ensure adequate ventilation of the working area.
<b>Storage</b>	Store in original container. Store at temperatures between 5 °C and 25 °C. Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure limits

Butanone (Butan-2-one (methyl ethyl ketone))	WEL 8-hr limit ppm: 200 WEL 15 min limit ppm: 300	WEL 8-hr limit mg/m3: 600 WEL 15 min limit mg/m3: 899
---	--	--

n-Butyl acetate (Butyl acetate)	WEL 8-hr limit ppm: 150 WEL 15 min limit ppm: 200	WEL 8-hr limit mg/m3: 724 WEL 15 min limit mg/m3: 966
------------------------------------	--	--

<b>Respiratory protection</b>	Wear suitable respiratory equipment when necessary. Wear: Suitable respiratory equipment.
<b>Hand protection</b>	Chemical resistant gloves (PVC)
<b>Eye protection</b>	Avoid contact with eyes. In case of splashing, wear: Safety glasses.
<b>Protective equipment</b>	Avoid contact with eyes and skin.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Description</b>	Liquid.
<b>Colour</b>	Clear.
<b>Odour</b>	Pungent.
<b>Flash point</b>	7°C

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Stable.
<b>Materials to avoid</b>	Strong oxidising agents.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

<b>Corrosivity</b>	Irritating to eyes, respiratory system and skin.
<b>Repeated or prolonged exposure</b>	Repeated or prolonged exposure may cause dermatitis.

## 12. ECOLOGICAL INFORMATION

## 13. DISPOSAL CONSIDERATIONS

<b>General information</b>	Dispose of as special waste in compliance with local and national regulations.
----------------------------	--

Manufactured by: Humiseal Europe,  
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England  
Phone: 44-127-669-1100 Fax: 44-127-669-1227

## HuiSeal 1R32A-2

Revision 2  
Revision date 4-Aug-2006

## 14. TRANSPORT INFORMATION

## ADR/RID

UN 1263	Packing group II
Class 3	Hazard ID 33
Proper Shipping Name	
PAINT RELATED MATERIAL	

## IMDG

UN 1263	Packing group II
Class 3	Marine pollutant .
EmS Code F-E S-E	

## IATA

UN 1263	Packing group II
Class 3	Subsidiary risk -
Packing Instruction 307 (Cargo)	Maximum quantity 60 L
Packing Instruction 305 (Passenger)	Maximum quantity 5 L

## 15. REGULATORY INFORMATION

**Symbols** F - Highly flammable; Xi - Irritant



**Risk phrases** R11 - Highly flammable.  
R66 - Repeated exposure may cause skin dryness or cracking.  
R67 - Vapours may cause drowsiness and dizziness.

**Safety phrases** S16 - Keep away from sources of ignition - No smoking.

## 16. OTHER INFORMATION

**Text of risk phrases in Section 2** R10 - Flammable.  
R11 - Highly flammable.  
R36 - Irritating to eyes.  
R66 - Repeated exposure may cause skin dryness or cracking.  
R67 - Vapours may cause drowsiness and dizziness.

**Further information** The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. The information provided relates only to the product or material specified and does not apply if used in combination with other materials. Handle and store under inert gas. This product is not properly labelled for sale or use outside the EU.

**Revision** This document differs from the previous version in the following areas:  
14 - aDR/RID.  
14 - iMDG.  
14 - iATA.

Manufactured by: Humiseal Europe,  
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England  
Phone: 44-127-669-1100 Fax: 44-127-669-1227

Print date 4-Aug-2006