

PENETRATING OIL

8472-LIQUID

Material Safety Data Sheet

Section 1: Product and Company Identification

Product Name: Penetrating Oil

MSDS Code: 8472-Liquid

Related Part #: 8472-4L, 8472-20L

Manufacturer: MG Chemicals (Head Office), 9347-193 Street, Surrey, B.C., V4N 4E7

Emergency Contact: CANUTECH ☎: 1-613-996-6666, Collect 24/7

Technical Contacts: ☎ 1-800-201-8822 FAX 1-800-708-9888

E-MAIL: support@mgchemicals.com **WEB** www.mgchemicals.com

Use: To protect metal parts from rust and corrosion.

Section 2: Hazards Identification

Eyes	Causes severe eye irritation if splashed in eyes.
Skin	May cause mild skin irritation. Can cause redness, dryness, burning and skin burns.
Inhalation	Harmful if inhaled. May cause nose, throat and lung irritation. Inhalation of aerosol may cause irritation to the upper respiratory tract.
Ingestion	Harmful if swallowed. Aspiration hazard.
Chronic	Prolonged or repeated contact may cause various forms of dermatitis including folliculitis and oil acne. Long term intensive exposure to oil mist may cause benign lung fibrosis.

PENETRATING OIL

8472-LIQUID

Section 3: Hazardous Ingredients

CAS #	Chemical Name	Wt%	ACGIH TWA	OSHA PEL	OSHA STEL
64742-47-8	Aliphatic hydrocarbon (petroleum) hydrotreated	30-60%	100 mg/m ³	N/A	300 mg/m ³
see Note A)	Mineral oil / metal working oil	15-40%	5 mg/m ³	N/A	10 mg/m ³
92045-24-4	Gas oils petroleum (hydrotreated light) vacuum	7-13%	N/A	N/A	N/A
57855-77-3	Calcium alkylnaphthalenesulfonate/carboxylate	3-7%	N/A	N/A	N/A
68478-94-4	Poly(oxy-1,2-ethanediyl), a,a'-[[[3-(decyloxy)propyl]methyliminio]di-2,1-ethanediyl]bis[w-hydroxy-, branched, chlorides	0.5-1.5%	N/A	N/A	N/A
57-55-6	Propylene glycol	0.1-1%	474 mg/m ³	N/E	N/E

Note A) Non-hazardous components that are listed or exempted by WHMIS and DSL. The base mixture has the following CAS numbers: 8042-47-5, 64742-46-7, 64742-47-8, 64742-53-6, 64742-54-7, 64742-55-8, 72623-84-8, 72623-85-9, 72623-86-0, 72623-87-1, 178603-64-0, 178603-65-1, 178603-66-2, 445411-73-4

Section 4: First Aid Measures

Eyes	Flush eyes with water for 15 minutes. Check for and remove any contact lenses. Get medical aid if irritation persists.
Skin	Wipe skin with dry cloth; then wash with water and soap. Get medical aid if irritation persists.
Inhalation	Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.
Ingestion	Do not induce vomiting. Get medical aid. Call a poison centre or physician. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink.

PENETRATING OIL**8472-LIQUID****Section 5: Fire Fighting Measures**

Autoignition Temperature 218 °C **Flash Point** ~101.6 °C **LEL / UEL*** 1.0% / 10.1%

Extinguishing Media Use dry chemical, carbon dioxide, or chemical foam

Combustion Products Generates CO, CO₂, sulfur dioxide, nitric oxides, and smoke.

General Information Will burn if involved in a fire. Aerosol container may explode when exposed to high heat. Cool fire-exposed aerosols with water fog. Watch your step: spilled material is very slippery.

**LEL = Lower Explosive Limit (in % by volume); UEL = Upper Explosive Limit*

Section 6: Accidental Release Measures

Containment Remove all source of ignition. Dike and contain large spills. Caution, the material is slippery.

Cleaning For large spills, scoop off liquid into a plastic or metal container. For smaller amounts, sprinkle absorbent compound onto spill, then sweep into a plastic or metal container. Wipe up further residue with paper towel and place in container. Wash spill area with soap and water to remove the last traces of residue.

Disposal Dispose of spill waste according to local disposal regulations.

Section 7: Handling and Storage

Handling Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

Storage Store in dry and well-ventilated areas away for sources of ignition or incompatible substances. Do not expose to temperature above 45 °C [113 °F].

PENETRATING OIL

8472-LIQUID

Section 8: Exposure Controls/Personal Protection

Routes of Entry

Eyes, ingestion, inhalation, and skin.

Engineering Controls

Ventilation: Normal ventilation is adequate when used as directed. Use general or local exhaust ventilation to keep airborne concentrations below exposure limits.

Personal Protective Equipment

Eye protection: Wear appropriate protective eyeglasses or chemical safety goggles.

Skin Protection: Wear appropriate protective clothing to prevent skin contact. Use of protective gloves in butyl rubber, PVC, neoprene, nitrile or other impervious gloves.

Respiratory Protection: If exposed to mist from aerosol, wear respirator.

General Hygiene Considerations

Wash hands with water and soap after use.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Odor	Slight hydrocarbon	Appearance	Clear yellow/orange
Odor Threshold	Not established	Freezing Point	Estimated at -30 °C	Partition Coefficient	Not established
Boiling Point	246 °C	Vapor Pressure	0.01 mm/Hg @ 21 °C	Evaporation Rate	Not applicable
Specific Gravity	0.83	Solubility in Water	Insoluble	pH	Not applicable
Autoignition Temperature	218 °C	Flash Point	~101.6 °C	Vapor Density	~5 (Air = 1)

*LEL = Lower Explosive Limit; UEL = Upper Explosive Limit

PENETRATING OIL

8472-LIQUID

Section 10: Stability and Reactivity

Stabilities	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Mechanical or thermal oil mist generation. Temperature over 40 °C, ignition sources, and incompatible substances
Incompatibilities	Strong acids, bases, oxidizing agents, reactive metals like sodium, barium, and aluminum
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information

Sensitization (effects of repeated exposure)	May cause skin sensitization and other allergic reactions
Carcinogenicity (risk of cancer)	Not a carcinogen
Reproductive Toxicity (risk of sterility)	Not a reproductive hazard
Teratogenicity (risk of fetus malformation)	Not known to harm an unborn child
Mutagenicity (risk of heritable genetic effects)	Not a mutagen

PENETRATING OIL
Lethal Exposure Concentrations
8472-LIQUID

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation	LD50 inhalation	TLC _o inhalation
Aliphatic hydrocarbon (petroleum) hydrotreated	>8,000 mg/kg Rat	>4,000 mg/kg Rabbit		>2500 ppm 4h Rat	
Mineral oil / metal working oil (mist)	>5,000 mg/kg Rat	N/A	N/A	N/A	1000 mg/m ³ 4 w Rat
Gas oil (petroleum) hydrotreated light vacuum	>5,000 mg/kg Rat	>2,000 mg/kg Rabbit	N/A	4100 mg/m ³ mist 4h Rat	N/A
Calcium alkylnaphthalenesulfonate	2000 mg/kg Rat	>20 g/kg Rabbit	>18 000 mg/m ³ 1 h Rat	N/A	N/A
Poly(oxy-1,2-ethanediyl), a,a'-[[[3-(decyloxy)propyl] methyliminio]di-2,1-ethanediyl]bis[w-hydroxy-, branched, chlorides	N/A	N/A	N/A	N/A	N/A
Propylene glycol	21,000 mg/kg Rat	20,800 mg/kg Rabbit	>105 ppm 8 h Rat	N/A	2180 mg/m ³ Rat 6h 30 d intermittent

Section 12: Ecological Information

This product is not readily Biodegradable. The CAS # 92045-24-4 component is a marine pollutant. It has a NOEC (no observed effect concentration) of 0.083 mg/mL for fish.

Consumer Products

VOC* (Californian & Canadian with LVP-VOC exemption) = 0.19% [1.6 g/L]

Commercial Products

VOC (Europe and WHIMS) = 38% [317 g/L]

VOC (EPA) = 71% [592 g/L]

*VOC = Volatile Organic Content; LVP-VOC = Low Vapor Pressure Volatile Organic Content

PENETRATING OIL

8472-LIQUID

Section 13: Disposal Information

Dispose of in accordance with all local, provincial, state, and federal regulations. As a general guideline, Canadian federal installations are limited to 15 mg/L total oil and grease discharge.

Section 14: Transport Information

Ground (4 Liter size)

Consumer Commodity; ORM-D

(20 Liter size)

Recommend Shipper be trained and certified. Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA CFR 49 Regulations** (Parts 100 to 185).

UN number: UN3082; **Shipping Name:** Environmentally Hazardous Substance, Liquid N.O.S. (Vacuum Gas Oil), **Class:** 9, PG: III

Air

Shipper must be trained and certified. Refer to IATA Dangerous Goods Regulations.

UN number: UN3082; **Shipping Name:** Environmentally Hazardous Substance, Liquid N.O.S. (Vacuum Gas Oil); **Class:** 9, PG: III

Sea

Shipper must be trained and certified. Refer to IMDG regulations.

UN number: UN3082; **Shipping Name:** Environmentally Hazardous Substance, Liquid N.O.S. (Vacuum Gas Oil, Marine Pollutant); **Class:** 9, PG: III

PENETRATING OIL**8472-LIQUID****Section 15: Regulatory Information****Canada****WHMIS Classification**

B3 – Combustible Liquid; DB2 – Toxic (Aspiration hazard)

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All ingredients are listed on the DSL/NDSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

USA**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain any chemicals listed as hazardous air pollutants.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

None of the chemicals in this product have a reportable quantity.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain any chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, May 1, 1997 revision, USA).

This product does not contain any chemicals listed


PENETRATING OIL

8472-LIQUID

HMIS RATING

HEALTH:	2
FLAMMABILITY:	2
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA CODES



Europe

RoHS

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

PENETRATING OIL

8472-LIQUID

Section 16: Other Information

MSDS Prepared by Michel Hachey

Date of Preparation 23 June, 2011

Abbreviations

N/A Not Applicable

N/E Not Estimated

LD50 Lethal Dose 50%

LC50 Lethal Concentration 50%

TCLo Lowest published toxic concentration

VOC Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. M.G. Chemicals, Inc. believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with federal, state, and local regulations.